Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

MYRICA VQ40-1
LCD TV

Issue May 2006

Pages 2

Superb audio performance and a vibrant, cinema like image make the 40” LCD MYRICA ideal for home entertainment. Light and thin enough to hang on your wall, yet packed with cutting-edge features: it’s the perfect enhancement of your digital home.
40” (101.5 cm) LCD screen with excellent 1000:1 contrast ensures a stunning image. High-definition TV technology for tomorrow’s HDTV content. Integrated stereo speakers for breath-taking sound and improved picture-in-picture functionality (PIP) thanks to two internal tuners.

- **n** 40 inch wide screen LCD display
- **n** HD ready
- **n** High resolution 1366 x 768 pixels
- **n** 16.7 Mio colors
- **n** Viewing angle 178° horizontal, 178° vertical
- **n** High brightness 500 cd/m² and very high contrast (1000:1)
- **n** Precise reproduction of fast movements
- **n** Multi norm dual TV tuner (PAL/SECAM)
- **n** Multiple video inputs
- **n** Teletext (5000 pages)
- **n** Plug and Play (DDC 2B interface)
- **n** HDMI with HDCP support
- **n** Digital/Analogue PC input via DVI-I (DVI with HDCP)
- **n** Immune to external electromagnetic fields
- **n** 10 languages OSD menu
- **n** Country specific warranty
- **n** Made in Germany

Visible screen diagonal	40 inch (101.5 cm) XGA
Panel resolution	
Pixels	1366 x 768
Pixel pitch	0.648 x 0.648 mm
Picture size	885.17 x 497.66 mm
Peak brightness	500 cd/m²
Peak contrast	1000:1
Response time g/g avg	8 ms
Viewing angle typical	
Horizontal	178°
Vertical	178°
Options	
TV tuner	Twin Tuner VHF/UHF/cable
Standard	PAL B/G, D/K, I SECAM B/G, DK, L
Sound system	mono, stereo, dual tone
Teletext	5000 pages (FLOF/TOP)
Video I/O	
2x TV-RF In	IEC-connectors
1x TV-RF Out	Feed for second tuner
DVI-I	with HDCP support
HDMI	with HDCP support
SCART1	21-pin Scart (CVBS/RGB)
SCART2	21-pin Scart (CVBS/S-Video)
AV: Composite video in	RCA Component Y in
S-Video (In)	(4 pin Dim)
Component video	3x RCA (Y/Pb/Pr) (Y shared with Composite Video In)
PC (Input)	
DVI-I Resolutions (with HDCP support)	1360 x 768 60 Hz 1280 x 1024 75 Hz 1280 x 720 60 Hz 1024 x 768 60 Hz 848 x 480 60 Hz 800 x 600 60 Hz 720 x 400 70 Hz 640 x 480 60 Hz
Video	
480i, 480p, 576i, 576p, 720p, 1080i with HDCP /DVI /HDMI and Component In	
Audio characteristics	
2x RCA	S-video Audio In
2x RCA	Video/ Component Audio In
1x RCA	SPDIF (In)
1x RCA	1x Subwoofer
2x RCA	1x Audio line out
1x RCA	SPDIF out
Internal Speakers	7W(L) + 7W(R)

Electrical values	
Rated voltage	110 - 240 V
Frequency	50 - 60 Hz
Power draw	
Operating typical	270 W
Standby mode	< 3 W
Protection class	1
Temperatures / dimensions / weight	
Ambient temperature (to IEC721):	
Recommended range	15°C to 35°C
Limit	5°C to 35°C
Dimensions:	
(H x W x D)	617 x 989 x 114 mm
incl. stand	657 x 989 x 244 mm
Weight	approx. 24 kg (unpacked)
Compliance with standards	
Product safety	EN60065
Ergonomics	GS mark
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55013, EN55020B, EN55022/B, EN50024, 61000-3-2/-3)
Accessories	
Power cable 1 (1.8 m)	for wall socket Euro-Schuko-Type CEE7 plug type IEC-320-C13
Power cable 2 (1,8m)	UK plug
Scart cable	1,5m 21-pin
Antenna cable	1,5m IEC (female/male)
Remote control	incl. batteries (2x AAA)
User manual	multi language
Warranty booklet	
Getting Started	
Special features	
PIP (Picture in Picture)	
Various Zoom modes	
Automatic program search	
Cinema Mode	
Digital Audio In/Out	
Ordercode	
S26361-K1088-V170	
EAN	
4045827603115	

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers, 05/2006

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp